

K241 *“One litre top specification”*
Ambient Model

- Speed 500-15000Rpm
- Max Rcf 22000G
- Timer 0-99Minutes + hold
- Dims HWD 28x40x50Cms
- Weight 22.5Kilos



K241R *“The chill with all the frills”*
Refrigerated Model

- Speed 500-15000Rpm
- Max Rcf 22000G
- Timer 0-99Minutes + hold
- Dims HWD 35x40x62Cms
- Weight 45Kilos
- Temp -9 to +40C PID Controlled



Rotors - swing out available to both

BR5510 max speed 4000 Rpm 2,600G
 Swing out rotor 4 x 250ml max
 Requires tube adaptors

B5250 Buckets required set of 4
 (shown with Rotor)
 Sealed lids available B5419

BR5530 max speed 4000 Rpm 2,800G
 Microtitor plate buckets
 and rotor complete
 Capacity 4 total stacked



Rotors - fixed angle available to both



BRK5424

Adaptors available

max speed 15000 Rpm 22,000G
24 x 1.5-2.2ml tube, fixed angle rotor
Tube size maximum H40 x W11mm
Cap size dependant
8004/6 - 0.2-0.4ml
8004/8 - 0.5ml



BRK5436

max speed 15000 Rpm 22,000G
36 x 0.5ml tube, fixed angle rotor
Tube size maximum H40 x W8mm
Cap size dependant



BRK5448

max speed 15000 Rpm 22,000G
48 x 0.2ml tube, fixed angle rotor
Tube size maximum H40 x W6mm
Cap size dependant



BR5624

Adaptors available

max speed 4000 Rpm 2,250G
24 x 15ml tube, fixed angle rotor
Tube size maximum H120 x W17 mm
Cap size dependant
8009 - 5-10ml
8009/S - 2-4ml



BR5608

Adaptors available

max speed 4000 Rpm 2,250G
8 x 50ml tube, fixed angle rotor
Tube size maximum H115 x W30mm
Cap size dependant
6006 - 25ml
6007 - 15ml



BRK5690

max speed 9000 Rpm 15,000G
6 x 100ml tube, fixed angle rotor
Tube size maximum H125 x W45mm
Cap size dependant



BRK5695

max speed 9000 Rpm 15,164G
6 x 250ml tube, fixed angle rotor
Tube size maximum H125 x W62mm
Cap size dependant